



professional control devices

MiniController

Vers. 01-21



Available in:



2 x 600W + 3 AMP

4 x 600W + 7 AMP

HYBRID AND MULTIFUNCTIONAL



www.cli-mate.pro

Control your environment



Serie: MG Type: MG-3 / MG-7

MiniController

Vers. 01-21

TIMER RELAY AND HYSTERESIS CONTROLLER

All-in-One Controller

Meant for switching lamps and heater, control the speed and the supply of the fans according to the temperature.

- Plug & Play
- Easy to use
- Ready to use
- Provided of high quality components

Hysteresis controller & Timer Relay

All-in-one controller

Extra inlet for a clip fan

Technical data

Temperature range	: 5-55°C
Power supply	: 1-fase 220/240V – 50Hz
Switching differentia	: 1°C per step (hysteresis)
Heater inlet	: Max. 3500 WATT
Lamp inlet	: Max. 600 WATT
Protection class	: IP44
Measures	: 250 x 220 x 120 mm



1 = TIMER RELAY

- 1a = a Lamp inlet
- 1b = Heater inlet
- 1c = Timer

2 = CLIMATE CONTROLLER

- 2a = Fan/s inlet
- 2b = DC inlet
- 2c = Fuses
- 2d = On-off-100%
- 2e = Set the desired temperature
- 2f = Set the min. Fan Speed
- 2g = Set the max. Fan Speed
- 2h = Set the bandwidth(hysteresis)
- 2i = Temperature sensor
- 2j = Supply

NOTE: **NEVER** surpass the maximum charge recommended (per inlet)



The design and the writing of this leaflet have been realized with the most thorough accuracy. We do not take responsibility for printing or typing mistakes.



= Max. 600W



Heater



Temperature



Bandwidth



Fan (min., max. speed)



Continue