



professional control devices

MiniController • HUMIDITY

Vers. 01-21



Available in:

2 x 600W + 3 AMP

4 x 600W + 7 AMP

HYBRID AND MULTIFUNCTIONAL

Control your environment



www.cli-mate.pro



Serie: MH
Type: MH-3 / MH-7

MiniController • HUMIDITY

Vers. 01-21

TIMER RELAY, HYSTERESIS CONTROLLER AND (DE)HUMIDIFIER

All-in-One Controller

Meant for switching lamps and heater, control the speed and the supply of the fans according to the temperature. This prototype also counts with a humidity environmental control, with two modes: Humidifier and Dehumidifier. It includes a double sensor of temperature and humidity.

- Plug & Play
- Easy to use
- Ready to use
- Provided of high quality components

All-in-one controller

Controls your (de)humidifier

Double sensor: Temperature & Humidity

Technical data

Temperature range	: 5-55°C
Humidity range	: 20-100% rH
Power supply	: 1-fase 220/240V – 50Hz
Switching differential	: 1°C / ±5% rH per step (hysteresis)
Heater inlet	: Max. 3500 WATT
Lamp inlet	: Max. 600 WATT
Protection class	: IP44
Measures	: 250 x 220 x 120 mm



- 1 = TIMER RELAY**
 1a = Lamp inlet
 1b = Heater inlet
 1c = Timer

- 2 = CLIMATE CONTROLLER**
 2a = Fan/s inlet 2b DC inlet
 2c = Fuses
 2d = On-off-100%
 2e = Set the desired temperature
 2f = Set the min. Fan Speed
 2g = Set the max. Fan Speed
 2h = Set the bandwidth(hysteresis)
 2i = Temperature sensor
 2j = Supply
 2k = Inlet for humidifier/dehumidifier
 2l = Set the desired humidity level
 2m = Choose the mode: Hum./Dehum.

NOTE: **NEVER** surpass the maximum charge recommended (per inlet)



The design and the writing of this leaflet have been realized with the most thorough accuracy. We do not take responsibility for printing or typing mistakes.